Alpha Air Freshener Spice ACCO Brands Australia Pty Ltd

Version No: 1.2 Safety Data Sheet according to Work Health and Safety Regulations and ADG requirements

Issue Date: 11/06/2024

Details of the distributor of the safety data sheet

S.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	Alpha Air Freshener Spice	
Synonyms	Not Available	
Proper shipping name	FLAMMABLE LIQUID, N.O.S. (contains ethanol)	
Other means of identification	5L - 3004020 (633020720RE)	

Relevant identified uses of the substance or mixture and uses advised against Air Freshener

Details of the manufacturer or supplier of the safety data sheet

Registered company name	ACCO Brands Australia Pty Ltd	Registered company name	Reward Hospitality
Address	Idress 17-19 Waterloo Street, Queanbeyan NSW 2620 Australia Address 1 Arthur Dixon Cou		1 Arthur Dixon Court, Yatala, QLD
Telephone	+61-2-96740900	Telephone	1800 473 927
Fax	Fax +61-2-96740910		Not Available
Website	www.accobrands.com.au	Website	Rewardhospitality.com.au
Email	sds.anz@acco.com	Email	yatala@rewardh.com.au

Emergency telephone number

Association / Organisation	Poisons Information Line	Poisons Information Centre
Emergency telephone numbers	13 11 26	13 11 26 (Australia)
Other emergency telephone numbers	13 11 26	Not Available

SECTION 2 Hazards identification

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Poisons Schedule	Not Applicable
Classification ^[1]	Flammable Liquids Category 3, Serious Eye Damage/Eye Irritation Category 1, Hazardous to the Aquatic Environment Acute Hazard Category 1
Legend:	1. Classified by Chernwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements

Hazard pictogram(s)	
Signal word	Danger

Hazard statement(s)

H226	Flammable liquid and vapour.
H318	Causes serious eye damage.
H400	Very toxic to aquatic life.

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P103	Read carefully and follow all instructions.	

Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P233	Keep container tightly closed.	
P280	Wear protective gloves, protective clothing, eye protection and face protection.	
P240	Ground and bond container and receiving equipment.	
P241	Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.	
P242	Use non-sparking tools.	
P243	Take action to prevent static discharges.	
P273	Avoid release to the environment.	

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P310	Immediately call a POISON CENTER/doctor/physician/first aider.	
P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.	
P391	Collect spillage.	
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].	

Precautionary statement(s) Storage

P403

P403+P235 Store in a well-ventilated place. Keep cool.

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
64-17-5	30-60	ethanol
68131-39-5	<10	alcohols C12-15 ethoxylated
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available	

SECTION 4 First aid measures

Description of first aid measur	es
Eye Contact	 If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs: Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

For acute or short term repeated exposures to ethanol:

- Acute ingestion in non-tolerant patients usually responds to supportive care with special attention to prevention of aspiration, replacement of fluid and correction of nutritional deficiencies (magnesium, thiamine pyridoxine, Vitamins C and K).
- Give 50% dextrose (50-100 ml) IV to obtunded patients following blood draw for glucose determination.
- Comatose patients should be treated with initial attention to airway, breathing, circulation and drugs of immediate importance (glucose, thiamine).
- Decontamination is probably unnecessary more than 1 hour after a single observed ingestion. Cathartics and charcoal may be given but are probably not effective in single ingestions.
- Fructose administration is contra-indicated due to side effects.

SECTION 5 Firefighting measures

Extinguishing media

- Alcohol stable foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
----------------------	--

Advice for firefighters

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. If safe, switch off electrical equipment until vapour fire hazard removed. Use water delivered as a fine spray to control fire and cool adjacent area. Avoid spraying water onto liquid pools. DO NOT approach containers suspected to be hot.
Fire/Explosion Hazard	 Liquid and vapour are flammable. Moderate fire hazard when exposed to heat or flame. Vapour forms an explosive mixture with air. Moderate explosion hazard when exposed to heat or flame. Vapour may travel a considerable distance to source of ignition. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO). Combustion products include: carbon monoxide (CO) carbon dioxide (CO2) other pyrolysis products typical of burning organic material.
HAZCHEM	•3Y

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb small quantities with vermiculite or other absorbent material. Wipe up. Collect residues in a flammable waste container.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. Consider evacuation (or protect in place). No smoking, naked lights or ignition sources. Increase ventilation.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Safe handling	s, even those that have been emptied, may contain explosive vapours.

	 Do NOT cut, drill, grind, weld or perform similar operations on or near containers. Avoid all personal contact, including inhalation. Wear protective clothing when risk of overexposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. Avoid smoking, naked lights or ignition sources. Avoid generation of static electricity. DO NOT use plastic buckets.
Other information	 Store in original containers in approved flammable liquid storage area. Store away from incompatible materials in a cool, dry, well-ventilated area. DO NOT store in pits, depressions, basements or areas where vapours may be trapped. No smoking, naked lights, heat or ignition sources. Storage areas should be clearly identified, well illuminated, clear of obstruction and accessible only to trained and authorised personnel - adequate security must be provided so that unauthorised personnel do not have access. Store according to applicable regulations for flammable materials for storage tanks, containers, piping, buildings, rooms, cabinets, allowable quantities and minimum storage distances. Use non-sparking ventilation systems, approved explosion proof equipment and intrinsically safe electrical systems. Have appropriate extinguishing capability in storage area (e.g. portable fire extinguishers - dry chemical, foam or carbon dioxide) and flammable gas detectors.

Conditions for safe storage, including any incompatibilities

Suitable container	 Packing as supplied by manufacturer. Plastic containers may only be used if approved for flammable liquid. Check that containers are clearly labelled and free from leaks. For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 cSt. (23 deg. C) For manufactured product having a viscosity of at least 250 cSt. (23 deg. C) Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with friction closures and (iii) low pressure tubes and cartridges may be used. Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packagings In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.
Storage incompatibility	 Avoid oxidising agents, acids, acid chlorides, acid anhydrides, chloroformates. Avoid strong bases.

SECTION 8 Exposure controls / personal protection

Control parameters

INGREDIENT DATA								
Source	Ingredient	Material name	TWA STEL		STEL	Peak	Notes	
Australia Exposure Standards	ethanol	Ethyl alcohol	ohol 1000 ppm / 1880 mg/m3			Not Available	Not Available	Not Available
Emergency Limits								
Ingredient	TEEL-1			TEEL-2			TEEL-3	
ethanol	Not Available	Not Available Not Available		Not Available	15000* ppm			
Ingredient	Original IDLH	Original IDLH Revised II				ised IDLH		
ethanol	3,300 ppm	3,300 ppm			Not Available			
alcohols C12-15 ethoxylated	Not Available	Not Available			Not Available			
Occupational Exposure Bandin	g							
Ingredient	Occupational E	Exposure Band Rating			Oc	cupational Exposur	e Band Limit	
alcohols C12-15 ethoxylated	E ≤ 0.1 ppm							
Notes:	adverse health		h exposi	assigning chemicals into ure. The output of this pro-	ocess	•		

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard 'physically' away from the worker and ventilation that strategically 'adds' and 'removes' air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.
	Employees exposed to confirmed human carcinogens should be authorized to do so by the employer, and work in a regulated area.

Page 5 of 12

Air Freshener Spice

Individual protection measures, such as personal protective equipment	
Eye and face protection	 Safety glasses with side shields. Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent] Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly.
Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber
Body protection	See Other protection below
Other protection	 Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent] Employees engaged in handing operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges. A respirator affording higher levels of protection may be substituted. [AS/NZS 1715 or national equivalent] Emergency deluge showers and eyewash fountains, supplied with potable water, should be located near, within sight of, and on the same level with locations where direct exposure is likely. Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels. For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood. Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood. Overalls. PVC protective suit may be required if exposure severe. Eyewash unit. Ensure there is ready access to a safety shower. Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity. For large scale or continuous use wear tight-weave non-static

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

'Forsberg Clothing Performance Index'.

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

Material	CPI
BUTYL	A
NEOPRENE	A
NATURAL RUBBER	С
NATURAL+NEOPRENE	С
NITRILE	С
NITRILE+PVC	С
PE/EVAL/PE	С
PVA	С
PVC	С
VITON	С

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as 'feel' or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the 'Exposure Standard' (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 5 x ES	Air-line*	A-2 P2	A-PAPR-2 P2 ^
up to 10 x ES	-	A-3 P2	-
10+ x ES	-	Air-line**	-

* - Continuous Flow; ** - Continuous-flow or positive pressure demand

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Ansell Glove Selection

Glove — In order of recommendation
MICROFLEX® 63-864
MICROFLEX® Diamond Grip® MF-300
AlphaTec® Solvex® 37-185
AlphaTec® 38-612
AlphaTec® 58-008
AlphaTec® 79-700
AlphaTec® Solvex® 37-675
TouchNTuff® 83-500
DermaShield™ 73-711
MICROFLEX® 73-847

The suggested gloves for use should be confirmed with the glove supplier.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Orange Liquid		
	1		
Physical state	Liquid	Relative density (Water = 1)	0.90-0.95
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	6-8	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	28	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Flammable.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled

The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

	co-ordination, and ve Animal testing shows The material has NO corroborating animal Inhalation of high cor dizziness, slowing of	rtigo. that the most common signs of inhalation of been classified by EC Directives or other or human evidence. Incentrations of gas/vapour causes lung irrita reflexes, fatigue and inco-ordination.	verdose classific tion with	e accompanied by sleepiness, reduced alertness, loss of reflexes, lack of e is inco-ordination and drowsiness. eation systems as 'harmful by inhalation'. This is because of the lack of h coughing and nausea, central nervous depression with headache and rial during the course of normal handling, may be damaging to the health
	Ingestion of ethanol (Effects on the body:	ethyl alcohol, 'alcohol') may produce nause	a, vomit	ing, bleeding from the digestive tract, abdominal pain, and diarrhoea.
	Blood concentration	Effects		
	<1.5 g/L	Mild: impaired vision, co-ordination and reaction time; emotional instability		
Ingestion	1.5-3.0 g/L	Moderate: Slurred speech, confusion, inco-ordination, emotional instability disturbances in perception and senses, possible blackouts, and impaired objective performance in standardized tests. Possible double vision, flushing, fast heart rate, sweating and incontinence Slow breathing may occur rarely and fast breathing may develop in cases of metabolic acidosis, low blood sugar and low blood potassium. Central nervous system depression may progress to coma.		
	3-5 g/L	Severe: cold clammy skin, low body temperature and low blood pressure. Atrial fibrillation and heart block have bee reported. Depression of breathing may occur, respiratory failure may follow serious poisoning, choking on vomit may result in lung inflammation and swelling.		
	corroborating animal	-		ation systems as 'harmful by ingestion'. This is because of the lack of e individual.
Skin Contact	models). Nevertheles setting. Open cuts, abraded o Entry into the blood-s	ss, good hygiene practice requires that expo or irritated skin should not be exposed to this	sure be s materi s or lesi	ions, may produce systemic injury with harmful effects. Examine the skin
Eye	Direct contact of the	. , .		stinging and burning sensation, with reflex closure of the lid, and a unctiva. Discomfort may last 2 days but usually the injury heals without
Chronic	There is sufficient ev Toxic: danger of serio This material can cau produce severe defe Ample evidence exis Substance accumula	idence to suggest that this material directly of bus damage to health by prolonged exposur- use serious damage if one is exposed to it for cts. Its that this material directly causes reduced tion, in the human body, may occur and may	causes o e throug or long p fertility / cause	e, involving difficulty breathing and related whole-body problems. cancer in humans. gh inhalation, in contact with skin and if swallowed. beriods. It can be assumed that it contains a substance which can some concern following repeated or long-term occupational exposure. e scarring. It may also worsen damage caused by other agents.
				1
Air Freshener Spice	TOXICITY			IRRITATION
	Not Available			Not Available
	TOXICITY		IRRIT	ATION
	Dermal (rabbit) LD5	0: 17100 mg/kg ^[1]	Eye (ra	abbit): 500 mg SEVERE
	Inhalation (Rat) LC5	50: 64000 ppm4h ^[2]	Eye (ra	abbit):100mg/24hr-moderate
ethanol	Oral (Rat) LD50: 70	60 mg/kg ^[2]	Eye: a	dverse effect observed (irritating) ^[1]
etianoi			Eye: n	o adverse effect observed (not irritating) ^[1]
			Skin (r	rabbit):20 mg/24hr-moderate
				rabbit):400 mg (open)-mild
			Skin: r	no adverse effect observed (not irritating) ^[1]
alcohols C12-15 ethoxylated	ΤΟΧΙΟΙΤΥ		IRRITA	TION

Derm	al (rabbit) LD50: >2000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
Oral (Rat) LD50: 1600 mg/kg ^[2]	Eye: SEVERE *
		Skin: no adverse effect observed (not irritating) ^[1]
		Skin: slight

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

Skin Irritation/Corrosion Serious Eye Damage/Irritation Respiratory or Skin			
Skin Irritation/Corrosion	×	STOT - Single Exposure	×
	×	Reproductivity	×
Acute Toxicity	×	Carcinogenicity	×
ALCOHOLS C12-15 ETHOXYLATED	for Tergitol 25-L-9: Neodol 25-9 Neodol 25-7 *Shell Can Polyethers (such as ethoxylated surfactants and polyeth mixtures of oxidation products. Animal testing reveals that whole the pure, non-oxidised oxidization products also cause irritation. Humans have regular contact with alcohol ethoxylates th cleaning products. Exposure to these chemicals can occ toxicity show that relatively high volumes would have to has ever been reported. Studies show that alcohol ethox Animal studies show these chemicals may produce gas severe irritation occurred when undiluted alcohol ethox of genetic toxicity or potential to cause mutations and ca Some of the oxidation products of this group of substam As they cause less irritation, nonionic surfactants are off Both laboratory and animal testing has shown that there cancer. No adverse reproductive or developmental effect Tri-ethylene glycol ethers undergo enzymatic oxidation 1 cause depressed reflexes, flaccid muscle tone, breathin exposure may cause dose dependent damage to the kid The material may produce severe irritation to the eye ca produce conjunctivitis.	hylene glycols) are highly susceptible d surfactant is non-sensitizing, many of hrough a variety of industrial and con- cur through swallowing, inhalation, or occur to produce any toxic response. xylates have low toxicity through swal trointestinal irritation, stomach ulcers, cylates were applied to the skin and ej ancers. Toxicity is thought to be subst ces may have sensitizing properties. ten preferred to ionic surfactants in to a is no evidence for alcohol ethoxylate cts were observed. to toxic alkoxy acids. They may irritate g difficulty and coma. Death may resu dneys as well as reproductive and devi-	of the oxidation products are sensitisers. The sumer products such as soaps, detergents and oth contact with the skin or eyes. Studies of acute No death due to poisoning with alcohol ethoxylate llowing and skin contact. hair standing up, diarrhea and lethargy. Slight to yes of animals. These chemicals show no indication antially lower than that of nonylphenol ethoxylates. pical products. is (AEs) causing genetic damage, mutations or e the skin and the eyes. At high oral doses, they ma ult in experimental animal. However, repeated velopmental defects.
ETHANOL	The material may cause skin irritation after prolonged on vesicles, scaling and thickening of the skin.	r repeated exposure and may produce	e on contact skin redness, swelling, the production
Air Freshener Spice	known as reactive airways dysfunction syndrome (RADS criteria for diagnosing RADS include the absence of pre asthma-like symptoms within minutes to hours of a docu airflow pattern on lung function tests, moderate to sever lymphocytic inflammation, without eosinophilia. RADS (the concentration of and duration of exposure to the irrit result of exposure due to high concentrations of irritating disorder is characterized by difficulty breathing, cough a	vious airways disease in a non-atopic umented exposure to the irritant. Other re bronchial hyperreactivity on methac or asthma) following an irritating inhal lating substance. On the other hand, i g substance (often particles) and is co	c individual, with sudden onset of persistent er criteria for diagnosis of RADS include a reversible choline challenge testing, and the lack of minimal ation is an infrequent disorder with rates related to ndustrial bronchitis is a disorder that occurs as a

SECTION 12 Ecological information

Toxicity

Air Freehener Spice	Endpoint	Test Duration (hr)		Species	Value		Source
Air Freshener Spice	Not Available	Not Available		Not Available	Not Available	e	Not Available
	Endpoint	Test Duration (hr)	Speci	es		Value	Source
	LC50	96h	Fish			42mg/L	4
ath an al	EC50(ECx)	96h	Algae	or other aquatic plants		<0.001mg/L	_ 4
ethanol	EC50	72h	Algae	or other aquatic plants		275mg/l	2
	EC50	96h	Algae	or other aquatic plants		<0.001mg/L	_ 4
	EC50	48h	Crusta	acea		2mg/L	4
	Endpoint	Test Duration (hr)	Species		Value		Source
	LC50	96h	Fish		>=0.42	23<=8.211mg/l	l 2
cohols C12-15 ethoxylated	NOEC(ECx)	72h	Algae or c	ther aquatic plants	0.013	mg/l	2
	EC50	72h	Algae or c	ther aquatic plants	0.031	mg/l	2
	EC50	96h	Algon or o	ther aquatic plants	0.7mg	/1	4

	EC50	48h	Crustacea	0.143mg/l	2
Legend:		quatic Toxicity Data 5. ECETO	CHA Registered Substances - Ecotoxicologic C Aquatic Hazard Assessment Data 6. NITE (1 3	,

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

For Ethanol: log Kow: -0.31 to -0.32; Koc 1: Estimated BCF= 3; Half-life (hr) air: 144; Half-life (hr) H2O surface water: 144; Henry's atm m3 /mol: 6.29E-06; BOD 5 if unstated: 0.93-1.67,63% COD: 1.99-2.11,97%;

ThOD : 2.1.

Environmental Fate: Terrestrial - Ethanol quickly biodegrades in soil but may leach into ground water; most is lost by evaporation. Ethanol is expected to have very high mobility in soil. Volatilization of ethanol from moist soil surfaces is expected to be an important fate process. The potential for volatilization of ethanol from dry soil surfaces may exist. Biodegradation is expected to be an important fate process for ethanol based on half-lives on the order of a few days for ethanol in sandy soil/groundwater microcosms.

Atmospheric Fate: Ethanol is expected to exist solely as a vapour in the ambient atmosphere. Vapour-phase ethanol is degraded in the atmosphere by reaction with photochemicallyproduced hydroxyl radicals; the half-life for this reaction in air is estimated to be 5 days.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethanol	LOW (Half-life = 2.17 days)	LOW (Half-life = 5.08 days)
Bioaccumulative potential		
Ingredient	Bioaccumulation	
ethanol	LOW (LogKOW = -0.31)	
Mobility in soil		
Ingredient	Mobility	
ethanol	HIGH (Log KOC = 1)	

SECTION 13 Disposal considerations

Waste treatment methods	
Product / Packaging disposal	 Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Otherwise: If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Where possible retain label warnings and SDS and observe all notices pertaining to the product. Do NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material). Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

SECTION 14 Transport information

Labels Required	
Marine Pollutant	
HAZCHEM	•3Y

14.1. UN number or ID number	1993
14.2. UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (contains ethanol)
14.3. Transport hazard class(es)	Class 3 Subsidiary Hazard Not Applicable
14.4. Packing group	Ш
14.5. Environmental hazard	Environmentally hazardous
14.6. Special precautions for user	Special provisions223 274Limited quantity5 L

Air transport (ICAO-IATA / DGR)

14.1. UN number	1993		
14.2. UN proper shipping name	Flammable liquid, n.o.s. * (contains	ethanol)	
	ICAO/IATA Class	3	
14.3. Transport hazard class(es)	ICAO / IATA Subsidiary Hazard	Not Applicable	
01035(03)	ERG Code	3L	
14.4. Packing group	- 111		
14.5. Environmental hazard	Environmentally hazardous		
	Special provisions		A3
	Cargo Only Packing Instructions		366
	Cargo Only Maximum Qty / Pack		220 L
14.6. Special precautions for user	Passenger and Cargo Packing Instructions		355
4001	Passenger and Cargo Maximum Qty / Pack		60 L
	Passenger and Cargo Limited Qu	antity Packing Instructions	Y344
	Passenger and Cargo Limited Ma	uximum Qty / Pack	10 L

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	1993		
14.2. UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (contains ethanol)		
14.3. Transport hazard class(es)	IMDG Class IMDG Subsidiary Hazar	3 rd Not Applicable	
14.4. Packing group	II		
14.5 Environmental hazard	Marine Pollutant		
14.6. Special precautions for user	Special provisions 2	F-E , S-E 223 274 955 5 L	

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
ethanol	Not Available
alcohols C12-15 ethoxylated	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
ethanol	Not Available
alcohols C12-15 ethoxylated	Not Available

SECTION 15 Regulatory information

ethanol is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australian Inventory of Industrial Chemicals (AIIC)

alcohols C12-15 ethoxylated is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australian Inventory of Industrial Chemicals (AIIC)

Additional Regulatory Information

Not Applicable

National Inventory Status

National Inventory	Status		
Australia - AIIC / Australia Non-Industrial Use	Yes		
Canada - DSL	Yes		
Canada - NDSL	No (ethanol; alcohols C12-15 ethoxylated)		
China - IECSC	Yes		
Europe - EINEC / ELINCS / NLP	Yes		
Japan - ENCS	Yes		
Korea - KECI	Yes		
New Zealand - NZIoC	Yes		
Philippines - PICCS	Yes		
USA - TSCA	Yes		
Taiwan - TCSI	Yes		
Mexico - INSQ	Yes		
Vietnam - NCI	Yes		
Russia - FBEPH	Yes		
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.		

SECTION 16 Other information

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC - TWA: Permissible Concentration-Time Weighted Average
 PC - STEL: Permissible Concentration-Short Term Exposure Limit
 HARC: International Agency for Research on Cancer
 ACGIH: American Conference of Governmental Industrial Hygienists
 STEL: Short Term Exposure Limit
 FTEEL: Temporary Emergency Exposure Limit,
 IDLH: Immediately Dangerous to Life or Health Concentrations
 FCS: Exposure Standard
 FOSF: Odour Safety Factor
 NNOAEL: No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level

- ►TLV: Threshold Limit Value
- ►LOD: Limit Of Detection
- ►OTV: Odour Threshold Value
- ▶BCF: BioConcentration Factors
- ▶BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- ►PNEC: Predicted no-effect concentration

AIIC: Australian Inventory of Industrial Chemicals
 DSL: Domestic Substances List
 NDSL: Non-Domestic Substances List
 IECSC: Inventory of Existing Chemical Substance in China
 EINECS: European INventory of Existing Commercial chemical Substances
 FLINCS: European List of Notified Chemical Substances
 NLP: No-Longer Polymers
 FLICE: Civitize and New Chemical Substances

▶ ENCS: Existing and New Chemical Substances Inventory

- KECI: Korea Existing Chemicals Inventory
 NZIoC: New Zealand Inventory of Chemicals
 PICCS: Philippine Inventory of Chemicals and Chemical Substances
 TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
 INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
 FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.